

## Comparison of AWR300 and AWR250 Stickreader

Feature	AWR300	AWR250
	Signal a	(A)
Housing Details		
Dimensions (L x W x H)	650 x 85 x 42 mm	650 x 85 x 42 mm
Weight (approx.)	720 g	620 g
Ingress Protection	IP 67	IP 65
Read Range (with 30 mm ø cattle ear tag	g)	
HDX	30 cm	25 cm
FDX-B	30 cm	25 cm
Battery Endurance (approx.)		
Idle time	36 hrs	24 hrs
Normal Operation	Several Workdays	Several Workdays
Continuous Read	up to 12 hrs	up to 6 hrs
Charging time	3 hrs with Agrident supplied PSU	4 hrs with Agrident supplied PSU
Memory		1
In Groups	1,000,000 records	100,000 records
Task Mode	25 Tasks with 10,000	25 Tasks with 10,000
Database Function	Management Records each 10,000 Datasets	Management Records each
Keypad	10,000 Datasets	
Directional Pad		
		No. 100
OK Button	$\bigotimes$	$\mathbf{N}$
2 Softkeys	$\odot$	
Interface		
USB	VCP or MSD	VCP or MSD
RS232	With optional 2.5m cable	X
Bluetooth	4.0, Dual Mode (SPP, HID), BLE	4.1, Dual Mode (SPP, HID), BLE
WLAN	802.11 p/g/n up to 72.2 Mbps	X
Signalization		1
Display 2.4" color	$\bigotimes$	$\bigcirc$
Loudspeaker	$\bigcirc$	
LED on tip	$\mathbf{\tilde{\mathbf{v}}}$	×
Status LED	<b>Ö</b>	$\bigcirc$
Vibration Motor		
Accessories		
ALLESSUIRS	LISP and charging cable	USB cable
	USB and charging cable 12V Power Supply	AgriLink free download software
	AgriLink free download software	-/-
Optional Accessories		/
	Car Charger	Car Charger
	Car Charger Hard Case	Car Charger Hard Case